

Alarm System Transmitter FM4

HIGHLIGHTS

- Additional module for all keyboard-controlled alarm systems
- No installation of driver or additional software necessary
- Plug & Play
- No additional power supply required, power supply via USB
- Extensive equipment: lanyard (neckband with security opening), USB-connecting lead, Velcro tape for fixture (e.g. tables)
- Build-in USB-Hub for connecting mouse or keyboard, if no USB connector available
- Works with every key combination
- Wireless radio remote control for initiation of the alarm system
- Approved and recommended by the Federal Employment Agency Germany, Cordaware, Stiller Alarm and Dataport



GENERAL

- 2 years of guarantee
- Long battery runtime (approx. 5 years)
- Flexible expandable
- Developed and produced in Germany
- CE-certificated
- Individual leasing offers
- Competence trainings for handling FM4 concerning emergency relief / self-protection are optionally bookable

Alarm system transmitter FM4

| Model | 0100002 |
|----------------------------------|---|
| USB ports | 1 x plug + 1 x connector |
| Service voltage | 5V over USB |
| Range | 10m to 15m in cleared area |
| Components | USB-receiver box (grey), radio remote control (red) |
| Frequency | 433 MHZ |
| CE marking | Yes |
| Security | Only the programmed key combination will be transmitted. A misuse of the FM4 through hacker attacks is excluded. |
| Controls | Triggering key (grey) on remote control |
| Coding | Transmitter and receiver are aligned. The system only works as pre-defined set. |
| Compatible Emergency Call System | Federal Employment Agency (ARE), Cordaware (bestinformed Alarm Edition), Stiller Alarm (Alarm Software), Netcallup (NetAlarmPro), Dataport (Vocario) and all other keyboard-bound alarm systems |
| Available keyboard combination | All |
| Equipment | USB connecting lead (2m), neckband with security opening, 20 mm width, red with velcro tape self-retaining, operations manual |
| Voltage supply | 100-235 V AC (+/- 10%, 50-60 Hz) |
| Power input | Max. 0,5 W / 0,1 A |
| Temperature | +5° C to +45° C |
| Casing measures W x H x D cm | Receiver box: 8,5 x 3,2 x 6,5, Transmitter: 6,3 x 3,0 x 4,0 |
| Weight | Receiver box: 64g, Transmitter: 26g |

Technical Data